Technical Data Metal Switches

Series GC

Description GC-U1Z W

Operating symbol

 $\begin{array}{c} \textcircled{} \\ \textcircled{} \\ 11 \\ \cancel{} \\ 23 \\ \cancel{} \\ 24 \end{array}$


Operating diagram

Omm


1

1.8

4.5mm



Ø7



Blind hole for fitting pin Ø4; 5.5 deep

		Tolerances
		Operating point: ± 0,25mm;
ON	OFF	Actuating force: ± 10%

13.5N

4.2N

Electrical data		
Rated insulation voltage	Ui	400 VAC
Conv. thermal current	I _{the}	10 A
Rated operational voltage	Ue	240 V
Utilization category		AC-15, U _e /I _e 240 V / 3 A
Positive opening NC contact	Θ	acc. to IEC/EN 60947-5-1, Annex K
Short-circuit protective device		Fuse 10A gL/gG
Protection class		I

This document will not become the contractual basis; the details included herein do not constitute any descriptions of expected conditions, so that warranties/claims for defects on account of possible variations of the actual qualities from the qualities described herein are explicitly excluded. All rights reserved. Specifications subject to change without notice!

Bernstein AG, Tieloser Weg 6, D-32457 Porta Westfalica, Germany / www.bernstein-ag.de

Date of issue: 18.05.2006 / Page 1 of 2 Document: 6021103008_en.doc / Last update: 1 / 2396-06



Article number

6021103008

Technical Data Metal Switches



Mechanical data

Enclosure	Die-cast aluminium
Cover	Sheet aluminium
Actuator	Plunger (thermoplastic)
Ambient air temperature	-30°C +80°C
Contact type	1 NC, 1 NO (Zb)
Mechanical life	10 x 10 ⁶ operating cycles
Switching frequency	≤ 100 / min.
Assembly	2 x M4
Connection	4 screw terminals (M3,5)
Conductor cross-sections	Solid: 0.5 1,5 mm ²
	Litz wire with ferrules: 0,5 1,5 mm ²
Cable entrance	1 x cable gland (M20 x 1,5)
Weight	≈ 0,156 kg
Installation position	Operator definable
Protection type	IP65 acc. to IEC/EN 60529

Actuation

The push bolt actuator is mainly intended to be actuated along it's axis. Side actuation will considerably reduce switch life.

Standards

VDE 0660 T100, DIN EN 60947-1, IEC 60947-1 VDE 0660 T200, DIN EN 60947-5-1, IEC 60947-5-1

EU Conformity

CE

Approvals

cCSAus A300 (same polarity)

Notes

The specified protection classification (IP code) applies only when the cover is closed and the appropriate cable is used, in accordance with the clamping range of the above mentioned cable gland.

This document will not become the contractual basis; the details included herein do not constitute any descriptions of expected conditions, so that warranties/claims for defects on account of possible variations of the actual qualities from the qualities described herein are explicitly excluded. All rights reserved. Specifications subject to change without notice!

Date of issue: 18.05.2006 / Page 2 of 2 Document: 6021103008_en.doc / Last update: 1 / 2396-06