

# Handheld Mobile Computer



**KEY FEATURES** 

- ✓ 3.5"VGA or QVGA display
- ✓ Integrated 1D/2D barcode scanner
- 1.8m drop tolerance and IP65 sealing
- ✓ 3.8G HSPA+ or CDMA EVDO Rev. A and GPS
- ✓ 1GHz CPU and IEEE 802.11a/b/g/n
- ✓ Windows Embedded Handheld 6.5 / Android
- ✓ Numeric/QWERTY/AZERTY/QWERTZ
- ✓ Integrated 5MP auto focus camera
  - 4,000mAh battery



**Rugged Ergonomics** 



Latest Technologies



getting s

oicemail

text e-mail calendar

Flexible Communications



Powerful Performance

## Handheld Mobile Computer **HM50**



#### **INDUSTRIES**



Field Sales

FMCG

Government & Public Safety Healthcare Transportation & Logistics

#### SPECIFICATION

| PHYSICAL CHARACTERISTICS         |   |
|----------------------------------|---|
| DIMENSIONS (W X H X D)           | 75.8 x 154 x 28.6 mm / 2.9 x 6 x 1.1 inch   |
| WEIGHT                           | Including standard battery: 371g  |
| DISPLAY                          | 3.5" VGA with backlight, TFT-LCD, 260K, 480 x 640                                   |
|                                  | 3.5" QVGA with backlight, TFT-LCD, 260K, 240 x 320 (optional)                       |
| KEYPAD                           | Numeric / QWERTY / AZERTY / QWERTZ  |
| STANDARD BATTERY                 | Rechargeable, 3.7V, 4,000mAh, Li-ion  |
| BACKUP BATTERY (HOT SWAP)        | Rechargeable, 3.7V, 105mAh, Li-ion polymer (not customer-accessible or replaceable) |
| EXPANSION SLOT                   | Customer-accessible MicroSD slot for removable memory cards up to 32G               |
| SIM SLOT                         | 2 SIMs  |
| AUDIO                            | Speaker, Dual MIC Phone with noise cancellation, Bluetooth headset profile          |
| CAMERA                           | 5 megapixel color camera with LED Flash   |
| GPS                              | Integrated AGPS   |
| PERFORMANCE CHARACTERISTICS      |   |
| CPU                              | 1GHz  |
| OS                               | Windows Embedded Handheld 6.5 / Android   |
| MEMORY                           | 256MB RAM (optional 512MB) / 512MB ROM  |
| INTERFACE                        | RS-232C, USB 2.0 Host & Client via Snap-on  |
| USER ENVIRONMENT CHARACTERISTICS |   |
| OPERATING TEMP                   | -20°C to 60°C / -4°F to 140°F   |
| STORAGE TEMP                     | -25°C to 70°C / -13°F to 158°F  |
| HUMIDITIY                        | 95% non-condensing  |
| DROP SPEC                        | 6 ft./1.8 m drop per MIL-STD 810G   |
| SEALING SPEC                     | IP65  |
| INTEGRATED RADIO                 |   |
| WWAN RADIO                       | 3.8G GSM HSPA+/HSUPA or CDMA EVDO Rev. A  |
| WLAN RADIO                       | IEEE 802.11a/b/g/n  |
| WPAN RADIO                       | Bluetooth Class II V2.1   |
| DATA CAPTURE                     |   |
| BARCODE SCANNER                  | 1D&PDF417 Laser Class II or 1D&2D CMOS Imager                                       |

\* Please ask your sales representative for the specs not listed above.



BR-S-HM50-EN-CC012

Copyright © 1995-2012 Bluebird Soft Inc. All rights reserved. Bluebird Soft Inc. is the designer and manufacturer of Pidion handheld mobiles. Pidion and stylized Pidion Logo are registered trademarks and symbols of Bluebird Soft Inc. Features and specifications are subject to change without prior notice.

### Bluebird

Bluebird Soft Inc. (Corporate Headquarters) SEI Tower 13~14F, 467-14, Dogok-dong, Gangnam-gu, Seoul, Korea (ROK) Phone. +82.70.7730.8000 Fax. +82.2.548.0870

#### Bluebird USA Inc.

460 Bergen Blvd. Suite 202A, Palisades Park, NJ 07650 Phone. +1.201.944.0822 Fax. +1.201.944.3577

Website Global I bluebirdsoft.com EN I mypidion.com

